



PALIGHT®

Flat Foamed PVC Sheet



► Overview

PALIGHT is a lightweight, versatile, flexible, and durable foamed PVC sheet that is ideal for use in advertising and construction. PALIGHT exhibits the whitest available surface and was successfully tested by the majority of digital flatbed printer manufacturers. Printers and advertisers benefit from its constantly smooth and bright surface for producing high quality displays. PALIGHT is easily handled, cut and fabricated using conventional tools and equipment, and can be printed, painted or laminated.



► Main Benefits

- Tested and approved for digital printing
- Bright white, smooth and uniform surface
- Available in a wide range of standard and special designer color
- Standard matte or gloss finishes
- Good insulation, lower heat transmission
- Non-toxic
- Flammability: self-extinguishing
- Half the weight of solid PVC sheets
- Same thickness at lower cost
- Good mechanical properties
- Easily worked with conventional tools, prints and paints
- Can be easily bonded, vacuum formed, nailed and bolted
- Low water absorption
- High chemical resistance
- Meet various international standards



► Typical Applications

Advertising - Signs, displays, interior decoration, exhibition graphics, cladding etc.

Construction - Models, partitions, wall cladding, interior decoration, air conditioning ducts, etc..

Industry - Control cabinets and panels, structures for corrosive environments, ducts, etc.

Serigraphy (Screen Printing) - PALIGHT's flat, consistent surface makes it ideal for screen printing. It is suitable for use with aqueous and solvent-based inks. PALIGHT's sheet surface has low absorption giving excellent ink yield.

Digital Printing - PALIGHT was approved by major digital flatbed printer manufacturers, and is suitable for use with digital inks and UV curing. All 1-10mm white PALIGHT sheets have a bright and smooth surface for true color interpretation.



► Standard Dimensions

Specification	PALIGHT® (mm)	PALIGHT® 2001(mm)	
Thickness	1-13, 15, 19, 25	3 - 10	WHITE
Dimensions*	1220x2440, 1560x3050 2030x3050	1220x2440 1220x3050	
Color	Colors Standard & Designer Colors	Black, Gray, Red, Blue, Yellow, Green, White	COLORS
Thickness	3 - 10	3 - 5	
Dimensions*	1220x2440 2030x3050	1220x2440 1220x3050	

*Special dimensions are available upon request.

► PALIGHT® Product Range

Product	Description
PALFOAM™	Low-weight flat foamed PVC sheet with matte finish. Available in white only.
PALIGHT®	Flat foamed PVC sheet with matte finish, available in a wide range of standard and special designer colors.
PALIGHT® 2001	Flat foamed PVC sheet with glossy hard surface on one side, available in white and standard colors.

► Typical Physical Properties

Property	(ASTM Method)	Conditions	Units	Value
Density	(D-792)		g/cm ³	0.55-0.7*
Water Absorption	(D-570)	24 hr. @ 23 °C	%	0.5-0.8**
Flexural Strength at Yield	(D-790)	1mm/min.	MPa	28*
VICAT Softening Temp	(D-1525)	Load: 1kg	°C	75
Coefficient of Linear Thermal Expansion	(D-696)		cm/cm °C	6.7x10 ⁻⁵
Thermal Conductivity	(C-177)		W/mK	0.06-0.07**
Surface Resistance	(D-257)		Ohm	5X10 ¹⁵
Volume Resistance	(D-257)		Ohm-cm	2X10 ¹⁶

*Results refer to 3mm sheet ** Depending on thickness (3-10mm)

► Flammability

PALIGHT is self extinguishing and complies with the most demanding international fire resistance standards defined in the field of plastics, as indicated by representative results in the attached table.

Standard	Classification*
DIN 4102	B-1
BS 476/7	Class 1
NSP 92501,5	M-1, M-2
UL 94	V-0

*Depends on thickness, type and color.

Inasmuch as PALRAM Industries has no control over the use to which others may put the material, it does not guarantee that the same results as those described herein will be obtained. Each user of the material should make his own tests to determine the material's suitability for his own particular use. Statements concerning possible or suggested uses of the materials described herein are not to be construed as constituting a license under any PALRAM Industries patent covering such use or as recommendations for use of such materials in the infringement of any patent. PALRAM Industries or its distributors cannot be held responsible for any losses incurred through incorrect installation of the material. In accordance with our company policy of continual product development you are advised to check with your local PALRAM Industries supplier to ensure that you have obtained the most up to date information.

Europe
UK
Israel
USA
Australia
Far East



EUROPE
PALRAM EUROPE LTD.
Tel: +44-1302-380776
Fax: +44-1302-380788
sales.europe@palram.com
www.palram.com

PALRAM UK
Tel: +44-1302-380738
Fax: +44-1302-380788
sales.uk@palram.com

ISRAEL
PALRAM ISRAEL
Tel: +972-4-8459900
Fax: +972-4-8459980
palram@palram.com
www.palram.co.il

USA
PALRAM AMERICAS
Tel: +610-2859918
Fax: +610-2859928
palramamericas@palram.com
www.palramamericas.com

► PALIGHT® Color Chart

Standard Colors	Code	PANTONE®	RAL
White*	ST-10		
Yellow	ST-30	108U	-
Red	ST-50	1805C	-
Blue	ST-70	288C	-
Green	ST-80	3415C	-
Black	ST-90	4C 2X	9011
Grey	ST-100	430C	7037

*Whites are divided by thickness: 1-10mm: ST-10 12-25mm: Classic White

Designer Colors	Code	PANTONE®	RAL
Digital White	DE-11		
Cream	ST-20	-	9001
Antique Cream	DE-21	Warm Grey 2C	1013
Bright Yellow	ST-40	1235C	-
Lemon	DE-31	102C	-
Blaze Orange	DE-41	144U	-
Orange	DE-51	165C	2004
Firebrick Red	DE-61	485C	-
Burgundy	DE-71	187C	3001
Light Blue	ST-60	2935C	-
Steel Blue	DE-81	277C	-
Sapphire Blue	DE-91	2757C	5002
Turquoise	DE-101	337C	-
Mint Green	DE-111	348C	6024
Dark Green	DE-121	3308C	6005
Dark Grey	DE-131	431C	7012
Smoke Grey	DE-141	428C	7074
Dim Grey	DE-151	408C	-
Olive Green	DE-161	378C	-
Sea Green	DE-171	361C	6018
Lime green	DE-181	390C	-
Royal Blue	DE-191	287C	5002
Sky Blue	DE-201	299C	-
Cardinal Red	DE-211	200C	3031
Orchid Pink	DE-221	204C	-

